


## Non-Metallic Sheathed Cable Fittings

### Steel or malleable iron

### Two-Screw Connectors

Rounded cable grip and smooth bushing protect the cable sheath and wire insulation. Because saddle is threaded, screws do not travel or extend beyond the connector body as it is clamped to the cable. An extra lip on the saddle closes the unused part of the connector opening.

- Threaded saddle means screws don't travel or extend beyond connector body as it's clamped to cable
- Extra lip on saddle closes unused part of connector opening
- Steel or malleable iron construction
- Look for the unique T&B blue color ensuring the highest quality fitting



| NON-INSULATED<br>CAT. NO. | INSULATED<br>CAT. NO. | K.O.<br>SIZE | UL LISTED & CSA CERTIFIED                               |                                      | UL LISTED & CSA CERTIFIED<br>SERVICE<br>ENTRANCE CABLES                                         | IN.     |         |       | INSULATED CABLE<br>OPENING (IN.) |       |
|---------------------------|-----------------------|--------------|---------------------------------------------------------|--------------------------------------|-------------------------------------------------------------------------------------------------|---------|---------|-------|----------------------------------|-------|
|                           |                       |              | SINGLE<br>NM & NMC CABLE                                | PAIRS OF<br>NM & NMC CABLE           |                                                                                                 | A       | B       | C     | MAX.                             | MIN.  |
| 3302-TB*                  | 3302M-TB              | 1/2"         | (2) #14, (2) #12, (2) #10,<br>(3) #14, (3) #12, (3) #10 | (2) #14, (2) #12                     | (2) #12 thru (2) #4, (3) #12, (3) #10                                                           | 1       | 1 13/32 | 1     | .590                             | .250  |
| 3303-TB                   | 3303M                 | 3/4"         | (2) #8, (2) #6, (3) #8,<br>(3) #6, (3) #4               | (2) #12, (2) #10,<br>(2) #8, (3) #14 | (2) #8 thru (2) 1/0, (3) #8, (3) #6,<br>(2) #6 + #8 GND,<br>(2) #1, (2) 1/0, (3) #6 thru (3) #2 | 1 1/4   | 1 1/8   | 1 1/4 | .750                             | .530  |
| 3304                      | 3304M                 | 1"           | (3) #8, (3) #6, (3) #4                                  | (2) #8, (3) #10                      | (2) #4 + #6 GND, (2) #3 + #5<br>GND, (2) #2 + #4 GND<br>(3) #2 thru (3) 2/0, (2) #1 + #3 GND    | 1 1/2   | 1 1/8   | 1 1/4 | .990                             | .690  |
| 3305                      | 3305M                 | 1 1/4"       | —                                                       | (2) #8, (2) #6, (2) #4, (3) #8       | (2) 1/0 + #2 GND,<br>(2) 2/0 + #1 GND                                                           | 1 5/8   | 2 1/4   | 1 1/4 | 1.320                            | .850  |
| 3306                      | 3306M                 | 1 1/2"       | (3) #4, (3) #6                                          | —                                    | (3) 3/0, (3) 4/0, (2) 3/0 + 1/0<br>GND, (2) 4/0 + 2/0 GND                                       | 2 1/8   | 2 1/8   | 1 1/8 | 1.530                            | .930  |
| 3307                      | 3307M                 | 2"           | Max. 1.98", Min. 1.15"                                  | Max. 1.98", Min. 1.15"               | —                                                                                               | 2 3/4   | 3 3/4   | 1 1/8 | —                                | —     |
| 3308†                     | —                     | 2 1/2"       | Max. 2.38", Min. 1.5"                                   | Max. 2.38", Min. 1.5"                | —                                                                                               | 3 1/4   | 3 5/8   | 2 3/8 | —                                | —     |
| 3309†                     | —                     | 3"           | Max. 2.88", Min. 1.75"                                  | Max. 2.88", Min. 1.75"               | —                                                                                               | 3 11/16 | 4 1/8   | 2 1/8 | 1.980                            | 1.150 |
| 3310†                     | —                     | 3 1/2"       | Max. 3.38", Min. 2.25"                                  | Max. 3.38", Min. 2.25"               | —                                                                                               | 4 1/8   | 5 1/4   | 2 3/4 | —                                | —     |
| 3311†                     | —                     | 4"           | Max. 3.88", Min. 2.5"                                   | Max. 3.88", Min. 2.5"                | —                                                                                               | 4 3/8   | 5 15/16 | 3 1/4 | —                                | —     |

\*UL Listed for use with rubber and thermoplastic flexible cords (both single and multiple cords and two oval cables).

UL Listed for multiple cords and cables.

CSA File No. 2884

UL File No. E-23013 — 1/2" — 1 1/2"; U.L. File No. E-15170 — 2"

† Not UL Listed or CSA certified.