

Gemeinsame Daten		
Schirmungsmaß		
30 - 300 MHz	[dB]	> 85
300 - 470 MHz	[dB]	> 80
470 - 862 MHz	[dB]	> 75
Allgemeine Daten		
Anschlüsse	[dB]	F-Buchsen
Schirmungsmaß		Klasse A gem. EN 50083-2
Impedanz	[Ω]	75

Typ		HFD 111			HFD 212				
Bestellnummer		414 140			414 150				
EAN-Code		402618320089			402618320102				
		1-fach Abzweiger			2-fach Abzweiger				
Frequenzbereich	[MHz]	5...2400							
Verteildämpfung									
5 - 40 MHz	[dB]	10,5			10,5				
40 - 1000 MHz	[dB]	10,5			11				
1000 - 2050 MHz	[dB]	12			11,5				
2050 - 2400 MHz	[dB]	13,5			13				
Durchgangsdämpfung									
5 - 40 MHz	[dB]	2,5			3,5				
40 - 1000 MHz	[dB]	1,5			2,5				
1000 - 2050 MHz	[dB]	3,0			4,5				
2050 - 2400 MHz	[dB]	4,0			5,5				
Entkopplungsdämpfung									
		Stich / Stamm			Stich / Stamm		Stich / Stich		
5 - 40 MHz	[dB]	10,5			17		15		
40 - 1000 MHz	[dB]	10,5			25		30		
1000 - 2050 MHz	[dB]	12			20		25		
2050 - 2400 MHz	[dB]	13,5			15		20		
Reflexionsdämpfung									
		Eingang	Ausgang	Stich		Eingang	Ausgang	Ausgang	Stich
5 - 40 MHz	[dB]	11	13	5		8	13	10	5
40 - 1000 MHz	[dB]	14	12	14		14	12	14	13
1000 - 2050 MHz	[dB]	14	10	14		15	10	15	12
2050 - 2400 MHz	[dB]	8	10	10		8	10	10	10